

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

| | | | | | |
|------------------------|-------------------|-----------------|---------------------------------|------|-------|
| 1 a CERTIFICATE NUMBER | b REVISION NUMBER | c DOCKET NUMBER | d PACKAGE IDENTIFICATION NUMBER | PAGE | PAGES |
| 9185 | 8 | 71-9185 | USA/9185/B(U)-96 | 1 OF | 3 |

2 PREAMBLE

- a This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material "
- b This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U S Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be

3 THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION**a ISSUED TO (Name and Address)**

Industrial Nuclear Company, Inc.
14320 Wicks Blvd.
San Leandro, CA 94577

b TITLE AND IDENTIFICATION OF REPORT OR APPLICATION

Industrial Nuclear Company application
dated July 1, 1999, as supplemented.

4 CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below

5

(a) Packaging

(1) Model No.: OP-100

(2) Description

The Model No. OP-100 package consists of either an IR-50 source changer, or an IR-100 exposure device, which is positioned within a 10 gallon drum. The drum is made of 20 gauge steel, and is closed with a 12 gauge closure ring and a 5/8 inch diameter steel bolt. Plywood members are used to position and support either the IR-50 or IR-100 within the steel drum.

The IR-50 source changer and the IR-100 exposure device are approximately 8.87 inches long, 4.5 inches wide, and 8.5 inches high. The radioactive material contents consist of iridium-192 in source assemblies that meet the requirements for special form material. The source assemblies are positioned within a zircalloy or titanium "S" tube within the IR-50 or IR-100. The "S" tube is surrounded by a shield assembly made of depleted uranium. The uranium shield assembly is encased in a stainless steel housing. The space between the uranium shield assembly and the stainless steel casing is filled with a rigid polyurethane foam. The maximum weight of the IR-50 source changer is 55 pounds, the maximum weight of the IR-100 exposure device is 53 pounds, and the maximum gross weight of the Model No. OP-100 package is 77 pounds.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

| 1 | a CERTIFICATE NUMBER | b REVISION NUMBER | c DOCKET NUMBER | d PACKAGE IDENTIFICATION NUMBER | PAGE | PAGES |
|---|----------------------|-------------------|-----------------|---------------------------------|------|-------|
| | 9185 | 8 | 71-9185 | USA/9185/B(U)-96 | 2 OF | 3 |

(3) Drawings

The packaging is constructed in accordance with Industrial Nuclear Company Drawing Nos.: OP 100-1, Rev. 5, IR 50-1A, Rev. 3, IR 50-1B, Rev. 1, IR 100-1A, Rev. 5, and IR 100-1B, Rev. 2.

5. (b) Contents

(1) Type and form of material

Iridium-192 as sealed sources that meet the requirements of special form radioactive material.

(2) Maximum quantity of material per package

120 Ci (4.44 TBq) (output)

Output curies are determined in accordance with American National Standard N432-1980, "Radiological Safety for the Design and Construction of Apparatus for Gamma Radiography."

6. The source shall be secured in the shielded position of the packaging by the source assembly lock, lock cap, and the shipping plug (IR-100 only). The source assembly lock, lock cap, and the shipping plug (IR-100 only), must be fabricated of materials capable of resisting a 1475°F fire environment for one-half hour and maintaining their positioning function. The ball stop of the source assembly must engage the source assembly lock. The flexible cable of the source assembly and shipping plug must be of sufficient length and diameter to provide positive positioning of the source in the shielded position.
7. The name plate on the overpack must be fabricated of materials capable of resisting a 1475°F fire environment for one-half hour and maintain its legibility. The two vent holes in the side of the overpack must be covered with tape or rubber (plastic) plugs to prevent entry of rain water.
8. In addition to the requirements of Subpart G of 10 CFR Part 71:
 - (a) The package shall be prepared for shipment in accordance with the Operating Procedures of Chapter 7 of the application and
 - (b) Each package must meet the Acceptance Tests and Maintenance Program of Chapter 8 of the application.
9. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

| 1 | a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGES |
|---|-----------------------|--------------------|------------------|----------------------------------|------|-------|
| | 9185 | 8 | 71-9185 | USA/9185/B(U)-96 | 3 OF | 3 |

10. Revision No. 7 of this certificate may be used until February 28, 2010.
11. Expiration date: February 28, 2014.

REFERENCES

Industrial Nuclear Company application dated July 1, 1999.

Supplements dated: September 14 and December 29, 1999; October 24, 2003; March 22, and July 12, 2007, and November 25, 2008.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION



Eric Benner, Chief
Licensing Branch
Division of Spent Fuel Storage and Transportation
Office of Nuclear Material Safety
and Safeguards

Date: February 9, 2009



UNITED STATES
NUCLEAR REGULATORY COMMISSION
WASHINGTON, D.C. 20555-0001

SAFETY EVALUATION REPORT

Docket No. 71-9185
Model No. OP-100 Package
Certificate of Compliance No. 9185
Revision No. 8

SUMMARY

By application dated November 25, 2008, Industrial Nuclear Company, Inc., requested renewal of Certificate of Compliance No. 9185, for the Model No. OP-100 package. Industrial Nuclear Company, Inc., did not request any changes to the package design or authorized contents. The certificate has been renewed for a five year term.

EVALUATION

By application dated November 25, 2008, Industrial Nuclear Company, Inc., requested renewal of Certificate of Compliance No. 9185, for the Model No. OP-100 package. Industrial Nuclear Company, Inc., did not request any changes to the package design or authorized contents. The staff reviewed the documents referenced in the certificate and determined that the documentation was available and complete. The staff also reviewed the operating and maintenance procedures for the package and found them to be adequate.

The following changes have been made to the Certificate:

Condition No. 5(b)(2) of the certificate has been revised to include the corresponding quantity of Cobalt-60 in units of terabecquerel.

Condition No. 10, which authorizes use of the previous revision of the certificate for a period of approximately one year, was updated to reference Revision 7 of the Certificate of Compliance.

CONCLUSION

The certificate has been renewed for a five year term that expires on February 28, 2014. These changes do not affect the ability of the package to meet the requirements of 10 CFR Part 71.

Issued with Certificate of Compliance No. 9185, Revision No. 8,
on February 9, 2009